



SARATOGA PRODUCT SPECIFICATIONS

Plank Thickness: 5.0mm

IXPE Backing Thickness: 1.0mm

Total Product Thickness: 6.0mm

Product Width: 7.09"

Product Length: 48.03"

Wear Layer Thickness: 20 Mil Finish over Wear Layer: UV Coating

Planks per Carton: 8

Square Feet per Carton: 18.93 sq.ft.

Surface: Registered Embossed (EIR)

Scratch Resistant: Yes Stain Resistant: Yes

Floor Score® SCS Certified for indoor air quality

Ortho Phthalates: This product is Ortho Phthalate free Bio Fresh Guard
Anti Microbial Protection

INSTALLATION

Use: Residential and Commercial Rated

Installation Method: I4F Click System

Location: Can be Installed on any dry & leveled floor surface

Make sure your subfloor is clean, flat and level. You must fill in low spots (dips in subfloor) and flatten high spots (bumps in subfloor). Any subfloor that is not flat and/or level can cause the joints on the planks to break and the floor to separate over time. (NOTE: your floor must be level within 1/8" over 6' or 3/16" over a 10' radius.)

Leave an expansion gap of 1/4" around the perimeter of the room. Your flooring will expand and contract with temperature changes within the home as well as direct sunlight.

Do not install fixed objects such as cabinets on top on the floor.

Do not install quarter round moulding directly to the floor, attach it to the baseboard

SPECIAL FEATURES

Durable construction

Waterproof properties allows for installation in wet areas

High density attached under pad features Bio Fresh Guard Anti Microbial Protection

Registered embossing provides real wood look and feel

CLEANING AND MAINTENANCE

Saratoga vinyl planks can withstand topical water and water penetration without being damaged. Water leakage over or around the outer edges of the flooring however can damage a wood subfloor, so clean up water as soon as possible.

Sweep regularly to remove surface grit and dust.

Use a damp cloth or mop to clean up any dirt and footprints.

CAUTION: Planks are slippery when wet.

Never use wax, polish, abrasive cleaners or scouring agents as they may dull or distort the finish.

High heels can damage floors.

Do not allow pets with unclipped nails to scratch or damage the floor.

Use chair protectors, mats and rugs to help prevent scratching.

This is a high quality vinyl floor that if maintained, will last for years. If not protected properly, as with other floor covering such as hardwood and laminate, it will scratch. Scratches may be caused by pets, furniture, rocks from shoes, and many other abrasive items.

Use doormats at entrance way to protect the floor from discoloring. Avoid using rubber-backed rugs, as they may stain or discolor the rigid core vinyl flooring. If you have an asphalt driveway, use a heavy-duty doormat at your main door, as chemicals in asphalt can cause rigid core vinyl flooring to yellow.

Avoid exposure to direct sunlight for prolonged periods of time. Use drapes or blinds to minimize direct sunlight during peak sunlight hours.

Save a few planks in case of accidental damage. Planks can be replaced or repaired by a flooring professional.

If other trades are in the work area, a floor protector is highly recommended to help protect the finish of the floor.

WARRANTY

Lifetime Residential and 25 Year Light Commercial Limited Finish Warranty - see warranty guide for full details.

Customer Service Toll Free Number: 1-800 241 5754 **Email:**
info@unitedweavers.net